



Carbide Quick Change Grooving Bars

Groove Width	Minimum Bore	Offset	Max. Depth	Shank Length	Quick Change Shank ø	Uncoated Part#	AlTiN Coated Part #
.046	.185	.060	.200	.90	3/16	RQG427180	RQG427180A
	.185	.060	.300	.90	3/16	RQG427185	RQG427185A
	.185	.060	.400	1.10	3/16	RQG427190	RQG427190A
	.185	.060	.500	1.10	3/16	RQG427195	RQG427195A
	.185	.060	.600	1.30	3/16	RQG427200	RQG427200A
	.185	.060	.700	1.30	3/16	RQG427205	RQG427205A
.048	.185	.060	.200	.90	3/16	RQG427210	RQG427210A
	.185	.060	.300	.90	3/16	RQG427215	RQG427215A
	.185	.060	.400	1.10	3/16	RQG427220	RQG427220A
	.185	.060	.500	1.10	3/16	RQG427225	RQG427225A
	.185	.060	.600	1.30	3/16	RQG427230	RQG427230A
	.185	.060	.700	1.30	3/16	RQG427235	RQG427235A
.056	.185	.060	.200	.90	3/16	RQG427240	RQG427240A
	.185	.060	.300	.90	3/16	RQG427245	RQG427245A
	.185	.060	.400	1.10	3/16	RQG427250	RQG427250A
	.185	.060	.500	1.10	3/16	RQG427255	RQG427255A
	.185	.060	.600	1.30	3/16	RQG427260	RQG427260A
	.185	.060	.700	1.30	3/16	RQG427265	RQG427265A
.062	.185	.060	.200	.90	3/16	RQG427270	RQG427270A
	.185	.060	.300	.90	3/16	RQG427275	RQG427275A
	.185	.060	.400	1.10	3/16	RQG427280	RQG427280A
	.185	.060	.500	1.10	3/16	RQG427285	RQG427285A
	.185	.060	.600	1.30	3/16	RQG427290	RQG427290A
	.185	.060	.700	1.30	3/16	RQG427295	RQG427295A

Must be used with quick change bar toolholders on [page 499](#).

