



AlTiN Coated



Carbide Extreme Grooving Bars

Minimum Hole	Groove Width	Offset	Max. Depth	OAL	Shank ϕ	AlTiN Coated Part #
.5000	.062/.064	.150	.500	3	1/2	RGB221515
	.062/.064	.150	.750	3	1/2	RGB221520
	.062/.064	.150	1.000	3	1/2	RGB221525
	.062/.064	.150	1.250	3	1/2	RGB221530
	.062/.064	.150	1.500	3	1/2	RGB221535
	.093/.095	.150	.500	3	1/2	RGB221540
	.093/.095	.150	.750	3	1/2	RGB221545
	.093/.095	.150	1.000	3	1/2	RGB221550
	.093/.095	.150	1.250	3	1/2	RGB221555
	.093/.095	.150	1.500	3	1/2	RGB221560
	.125/.127	.150	.500	3	1/2	RGB221565
	.125/.127	.150	.750	3	1/2	RGB221570
	.125/.127	.150	1.000	3	1/2	RGB221575
	.125/.127	.150	1.250	3	1/2	RGB221580
	.125/.127	.150	1.500	3	1/2	RGB221585
	.156/.158	.150	.500	3	1/2	RGB221590
	.156/.158	.150	.750	3	1/2	RGB221595
	.156/.158	.150	1.000	3	1/2	RGB221600
	.156/.158	.150	1.250	3	1/2	RGB221605
	.156/.158	.150	1.500	3	1/2	RGB221610
	.187/.189	.150	.500	3	1/2	RGB221615
	.187/.189	.150	.750	3	1/2	RGB221620
	.187/.189	.150	1.000	3	1/2	RGB221625
	.187/.189	.150	1.250	3	1/2	RGB221630
	.187/.189	.150	1.500	3	1/2	RGB221635
	.250/.252	.150	.500	3	1/2	RGB221640
	.250/.252	.150	.750	3	1/2	RGB221645
	.250/.252	.150	1.000	3	1/2	RGB221650
.250/.252	.150	1.250	3	1/2	RGB221655	
.250/.252	.150	1.500	3	1/2	RGB221660	

Carbide Bars



Speeds, feeds and tech info pages 544-545.