









CAT40 Standard Retention Knobs

All retention knobs are compatible with all Haas CAT40 spindles. Retention knobs are also compatible with other manufacturers - please check your machine specifications to see if they are compatible with your equipment.





Machine Type	A	B	C	Angle	Thread Size	Hole ϕ	Torque Ft/lbs	Part #	Photo	Dimensions
Haas	.590	.390	1.270	45	5/8-11	—	30	RC4HRK		
Haas	.590	.390	1.270	45	5/8-11	.190	30	RC4HRKC		

CAT50 Standard Retention Knobs

All retention knobs are compatible with all Haas CAT50 spindles. Retention knobs are also compatible with other manufacturers - please check your machine specifications to see if they are compatible with your equipment.

Machine Type	A	B	C	Angle	Thread Size	Hole ϕ	Torque Ft/lbs	Part #	Photo	Dimensions
Haas	.910	.670	1.780	45	1-8	—	75	RC5HRK		
Haas	.910	.670	1.780	45	1-8	.310	75	RC5HRKC		

Vertical/Horizontal Setup Holding Fixture

Taper	Description	Photo	Mounting	Part #
CAT40	<ul style="list-style-type: none"> • Open design for easy access to retention knobs • Removable keylock for keyed or unkeyed use • High torque split clamp with ratchet handle, mar-free grip • Durable heat-treated premium grade aircraft aluminum 		 Mounts Vertically or Horizontally	RC4SE
CAT50	<ul style="list-style-type: none"> • Open design for easy access to retention knobs • Removable keylock for keyed or unkeyed use • High torque split clamp with ratchet handle, mar-free grip • Durable heat-treated premium grade aircraft aluminum 		 Mounts Vertically or Horizontally	RC5SE